FLAMMA

FC07
Overdrive Pedal
Owner's Manual

Content

Precautions0
Features 0
Гор panel 03-0
Effects Explanation 0
Specifications

Precautions

Please read carefully before proceeding

Power Supply

Please use power supply with 9V and at least 7mA current value for the unit. Incorrect power supply may cause short-circuit and damage.

Please turn off the power supply if the device is not used for long period.

Important Safety Instructions

- 1. Read these instructions
- 2. Keep these instructions
- 3. Heed all warnings
- 4. Follow all instructions
- 5. Do not use this apparatus near water
- 6. Clean only with a dry cloth
- **7.** Do not install near any ventilation openings. Install in accordance with the manufacturer's instructions
- **8.** Do not install near any heat sources such as radiators, heat registers, stoves or other apparati (including amplifiers) that produce heat
- **9.** Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade of the third prong are provided for your safety. If the provided plug does not fit into your outlet consult an electrician for replacement of the obsolete outlet
- **10.** Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point

FCC certification

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference
- This device must accept any interference received, including interference that may cause undesired operation

Features

- 1.2 Working Modes: Warm/Hot
- 2. True bypass switch
- 3. Very small and compact design
- **4.**DC 9V adapter power supply

Top panel



Top panel

- on TRUE BYPASS Footswitch: Push down the footswitch to toggle between on and bypass status.
- **ON/OFF LED:** Shows the on/off status of FC07, when the LED is lit the effect is engaged.
- **DC IN Power Jack:** For power supply, use a 9-volt DC regulated AC adapter (plug polarity is positive on the barrel and negative in the center).
- **1NPUT Jack:** 1/4" mono audio jack, for connecting guitar.
- **OUTPUT Jack:** 1/4" mono audio jack, outputs the signal.
- **Mode Switch:** Switch between Warm mode and Hot mode.
- **O7 VOLUME Knob:** Adjusts the volume of the overdrive sound.
- **OB TONE Knob:** Adjusts the tone color of the overdrive sound.
- **09 OVERDRIVE Knob:** Adjusts the gain of the overdrive sound.

Effects Explanation

Warm: Reconstruct a warm tube drive tone and nice dynamic response of classic tube amplifier, it provides a natural, smooth, creamy overdrive sound.

Hot: More powerful output than Warm mode, mighty crunch tone.

Specifications

Effects Modes: 2 (Warm, Hot)

Input: 1/4" monaural jack (impedance: 500k Ohms)

Output: 1/4" monaural jack (impedance: 10k Ohms)

Power Requirements: AC adapter 9V DC (center negative)

Current Draw: 7 mA

Dimensions: 47 mm (D) $\times 83 \text{mm}$ (W) $\times 52 \text{mm}$ (H)

Weight: 153g

Accessories: Safety Instruction & Warranty Card, Sticker, quick guide

*Notice: Recommend to use isolated/individual power supply. Sharing power supply with other pedals may cause unexpected noise.